



SENSOR SWITCH

Item #	RBS12	Description	TILT SWITCH	Version	V99.0
Page	1 of 3		Date	April 2, 2010	

● Functions

1. Rotation Detecting
2. Two way 45° Tilt Detecting

● APPLICATIONS

1. Automotive devices
2. Visual devices
3. Home electrical appliances
4. Information devices
5. Communication devices



● FEATURES

1. Tiny size, suitable for small space.
2. No electricity consumption during detection status.
3. Housing made of high insulation plastic material, free from electric conduction and rust problem.
4. Gold-plated ball and terminals, low possibility of oxidization.
5. All plastic materials subject to industrial purpose, resist high temperature and meet fireproof function.
6. Suitable to vertical PCB.
7. Simple ON and OFF signals, easy for design.
8. RoHS compliance, an ideal substitute for mercury switch.
9. A more economical tilt and rotation detection option than IC design solution.
10. All made in Taiwan and examined before shipment.

● PATENTS

1. Taiwan Patent No. I261280
2. U.S.A. Patent No. US 2008/0024956 A1
3. China Patent No. 200610078234.4



SENSOR SWITCH

Item #	RBS12	Description	TILT SWITCH	Version	V99.0
Page	2 of 3		Date	April 2, 2010	

● DIMENSIONS / OPERATION / P.C.B. LAYOUT (Unit: mm, Tolerance: ±0.25mm)

RBS 12 02 10	Tilt angle $\theta=45\pm 15^\circ$	P.C.B. Layout (DIP) / Top View

● ELECTRICAL CHARACTERISTICS

1.	Contact Rating	10mA, 5VDC
2.	Contact Resistance	10Ω max.
3.	Differential Angle	Refer to the drawing
4.	Insulation Resistance	10MΩ min. at 100VDC
5.	Dielectric Strength	100VDC min. for 1 minute
6.	Capacitance	5pF max.

● MECHANICAL CHARACTERISTICS

1.	Temperature Range	Operating: -25°C to +85°C Storage: -40°C to +85°C
2.	Pull Force of Terminal	500 gf for 1 minute
3.	Operation Life	100,000 cycles
4.	Humidity	95% RH, 40°C for 96 hrs.
5.	Solder Ability	After flux 260±5°C for 5±0.5 seconds 95% coverage

● BILL OF MATERIAL

1.	Housing	Liquid Crystal Polymer + Glass-Fiber
2.	Cu-Ball	Copper Alloy, Gold Plated over Nickel
3.	Terminal	Copper Alloy, Gold Plated over Nickel



SENSOR SWITCH

Item #	RBS12	Description	TILT SWITCH	Version	V99.0
Page	3 of 3		Date	April 2, 2010	

● PACKAGE

	Part Number	Package	Quantity	Total	Size
1.	RBS120210T	Reel	2,000 pcs	2,000 pcs	Diameter=30 ; Width= 1.7 (cm)
		Inner Box	3 Reels	6,000 pcs	36 x 34 x 7 (cm)
		Carton(1)	4 Boxes	8,000 pcs	37 x 36 x 31 (cm)
		Carton(2)	10 Boxes	60,000 pcs	70 x 36 x 38 (cm)

* Minimum Order Quantity: One Reel

● NOTE

1. Suggestion for Application : Application in occasions that require vibration functions, adding design of "ON DELAY" is recommended. For great vibration, Optical type products are recommended.
2. Suggestion Contact Rating: 5 mA.
3. For the continued product improvement as one of the company policy, specifications may change or update without notice. The latest information can be obtained through our sales offices. Normally, all products are supplied under our standard conditions.

● PRECAUTIONS FOR USE

1. If the products is intended to be used for other endurance equipments requiring higher safety and reliability such as life support system, space and aviations devices, disaster and safety system, it's necessary to make verification of conformity or contact us for the details before using.
2. Don't try to clean the switch with a solvent or similar substance after the soldering process.
3. The switch might be damaged if using the water-soluble flux.
4. Don't use the switch in the environment with high humidity or other bedewing possibility, as it may cause leaking among the terminals.
5. It might catch fire if the rating exceeds the specifications. Never use the switch beyond the rating.